A Division of Illinois Tool Works Inc.		
Date:		
Purchase Order No:		
Subject:	Type:	
Batch No		
We hereby certify that when tested at time of m 1. Meets the requirements of and has bee	nanufacture, the above material: en tested for sulfur and halogens according to:	
including 2005, 2006, 2008, 6 B. ASME Boiler and Pressure Ve Examination, including 1999,20 C. ASME Boiler and Pressure Ve	essel Code, 2004 & 2007 Edition, Section V, Nondestru & 2009b Addenda, Article 6 Paragraph T-640 and Articlessel Code, 1995, 1998, & 2001 Edition, Section V Non 000,2002, & 2003 Addenda, Article 6 Paragraph T-640 essel Code, 1986, 1989 and 1992 Edition, Section V, ng 1992 Addenda, Paragraph T-625, 1993 Addenda Pa	icle 24 as applicable. ndestructive and Article 24 as applicable. Nondestructive
D. ASTM E-165-92, ASTM E-165	5-94, ASTM E-165-95,ASTM E-165-02, and ASTM E-16	65-09 Paragraph 7.1.
E. MIL-STD-271F(SH), 27 June 1 June 1993).	1986, Paragraphs 5.3 and 5.3.1., including Notice 1 Pa	aragraph 5.6.1 (21,
F. NAVSEA T9074-AS-GIB-010/2	271, 30 April 1997, Paragraph 5.3.1 & 5.6.2, including N	Notice 1.
G. MIL-STD-2132D, 11 February 200	03, Paragraph 7.1, 7.1.2., 7.1.3, Appendix C, Paragraph 40	
The following test results were obtained:		
Sulfur: wt, % of r	residue. CL+F: wt, % of res	sidue
Cleaner residue (see note 3)	g/100g g/	/100ml
2. We further certify that this material does	s not contain mercury as a basic element and no merc	cury bearing equip-

ment was used in its manufacture.

**MAGNAFLUX®** 

Mathew Plamoottil - Quality Assurance Mgr.

Lynda Carle- Lab Technician.

Notes: 1. Our batch number appears on the bottom of all aerosol cans and on the label of all bulk containers.

- 2. Most specifications require test results stated in percent but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right.
- 3. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material

Form No. F-1568 R-9/09

3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60025 ■ TEL (847) 657-5300 ■ FAX (847) 657-5388



Date:	
Purchase Order No	
We hereby certify that the,  Batch No, supplied meets the requirements approved by the U.S. Air Force.	Type of AMS 2644E, and is
When tested according to paragraph 4.3.2., Sampling Plan A, the followin	g results were obtained.
4.2.2.1. Penetrant Tests:  Flash Point (PMCC), 3.3.3  Viscosity, 3.3.4( cs. Nominal)  Fluorescent Brightness, 3.3.8.3.2.(FP-4PE Standard)  Water Tolerance (Method A only), 3.3.8.5  Removability, 3.3.8.6	°F cs@100°F %
4.2.2.1 Emulsifier Tests: Flash Point (PMCC), 3.3.3 Viscosity, 3.3.4( cs. Nominal) Water Content (Method D only), 3.3.9.6	°F cs@100°F %
4.2.2.3. Developer Tests:  Developer Fluorescence, 3.3.10.2  Developer Removability, 3.3.10.4  Redispersibility, 3.3.10.5	<u>.</u>
3.3.11.5 Remover Tests: Penetrant Removal, 4.4.11.3.2	<u> </u>

We further certify that this material meets the requirements of ASTM E 1417, Paragraph 5.1.

**MAGNAFLUX®** 

Mathew Plamoottil - Quality Assurance Mgr.

Lynda Carle - Lab Technician.

Mathew Planooth